

**Certificate of Verification of a Reference Standard of Measurement in Accordance with
Regulation 13 of the National Measurement Regulations 1999 (Cth) in Accordance with the
National Measurement Act 1960 (Cth)**

Description of standard of measurement:

Baseline Name: **WALKAMIN** **Calibration Identification:** **QLD.WALK1.210905**

Electronic Distance Measurement Baseline consisting of 7 concrete pillars. Baseline is located within Scientific Reserve 1/SP269667 between Kennedy HWY and Carbeen Rd, Walkamin.

Permanent Distinguishing Marks: Numerals 0 to 6 marked on concrete pillars. See also Mark ID as stated in the table below.

Client: **Queensland Department of Resources**
Client Address: Refer to signatory contact details below **Postal Address:**
Contact Name: **Contact Number:**

Date of Verification: **5th September 2021**

Period of Verification: **2 years** (on the condition that baseline monuments remain undisturbed)

Date of Expiry of Certificate: **5th September 2023**

Values of Standard of Measurement:

The base linear distances herein are from Station 0 and have been established by point to point measurement, corrected for slope, offset and datum plane. The base alignment is from Station 0 to Station 6. Negative offsets are to the left of the line viewed from Station 0. Datum Plane is based on Reduced Level (RL): 600 metres.

Station	Mark ID	Reduced Level (m)	Offset (m)	Distance (m)	Uncertainty (m)*
0	194600	597.027	0.000	N/A	N/A
1	194601	597.254	-0.005	30.104	0.0006
2	194602	598.293	0.017	180.518	0.0008
3	194603	600.735	-0.003	451.267	0.0011
4	194604	603.727	0.007	782.180	0.0016
5	194605	606.174	0.017	992.773	0.0018
6	194606	607.178	0.000	1083.021	0.0020

* The stated uncertainty applies only to the distances in the table above. Distances are from Station 0.

Test Method: **CBD/041230.LTOLE_Baseline_Calibration_Procedure**

Testing performed as per stated procedures. Distances measured using a Leica TS60 total station and atmospheric conditions measured using three Delta OHM HD31 Multifunction Loggers. All equipment is calibrated by NATA accredited laboratories.

Test Conditions: Measurements performed on the date of verification between 9 am and 1 pm under mostly overcast conditions with the following average ambient atmospheric conditions:

Temperature 22.7 °C **Pressure 949.1 hPa** **Relative humidity 60.8 %**

Uncertainty of the Value(s): **$\pm (0.5 + 1.3 \times 10^{-3} \times L)$ mm (Where L is length in m)**

This uncertainty has been calculated in accordance with the principles in JCGM 100: 2008 *Evaluation of Measurement Data — Guide to the Expression of Uncertainty in Measurement*, and give intervals estimated to have a confidence level of 95% at the time of verification. Unless otherwise stated, a coverage factor (k) of 2.0 has been used. The uncertainties apply at the time of measurement only and take no account of any movement or other effects that may apply afterwards. When estimating the uncertainty at any later time, other relevant information should also be considered, including, where possible, the history of the stability of the baseline.

Verifying Authority: **Queensland Department of Resources**

Signature:  **Signatory:** **Isaac Aaron Stiller**
Position: **QLD State EDM Calibration Officer**
Date of Issue: **15 September 2021**

Facility Address: Level 17, 275 George St Brisbane, QLD 4000

Postal Address: GPO Box 2454 Brisbane, Queensland 4001

Phone: (07) 3330 4427

Facsimile: (07) 3896 3697

Email: isaac.stiller@resources.qld.gov.au

Being a person with powers delegated by the Director General of the Queensland Department of Resources, appointed as a verifying authority under Regulations 71 and 73 of the *National Measurement Regulations 1999* (Cth) in accordance with the *National Measurement Act 1960* (Cth), I hereby certify that the above standard is verified as a reference standard of measurement in accordance with the Regulations by the above named authority. Accredited for compliance with AS ISO/IEC 17025:2018. The measurements used to produce this report are from equipment calibrated by the National Measurement Institute and other NATA accredited facilities. The results of the tests and/or calibrations included in this document are consequently traceable to SI units through Australian/National standards.